

Joist Size	MiTek Stock No.	Ref. No.	Steel Gauge	Dimensions (in)				Fastener Schedule ³				DF/SP Allowable Loads (Lbs.) ²				Corrosion Finish	Code Ref.		
				W	H	D	A	Min/ Max	Header		Joist		Uplift ¹						
									Qty	Type	Qty	Type	Floor	Roof				160%	
													100%	115%	125%				
2 x 4	JL24	LU24	20	1-9/16	3	1-1/2	15/16	--	4	10d 16d	2	10d x 1-1/2	470 560	540 640	580 695	295			
	JL24IF-TZ	--	18	1-9/16	3-1/8	1-1/2	--	--	4	10d HDG 16d HDG	2	10d x 1-1/2 HDG	480 570	545 600	590 600	265			
	JUS24	LUS24	18	1-9/16	3-1/8	1-3/4	1	--	4	10d	2	10d	675	775	835	660			
	SUH24	U24	16	1-9/16	3-1/4	2	1-3/16	--	4	10d 16d	2	10d x 1-1/2	500 590	560 665	605 720	380			
	HD26	HU26	14	1-9/16	3-1/2	2-1/2	1-1/8	Min Max	4	16d	2 4	10d x 1-1/2	615	695	745	335 585			
	2 x 6	JL26	LU26	20	1-9/16	4-3/4	1-1/2	15/16	--	6	10d 16d	4	10d x 1-1/2	710 840	805 960	870 1045	600		
		JL26IF-TZ	LUC26Z	18	1-9/16	4-1/2	1-1/2	--	--	6	10d HDG 16d HDG	4	10d x 1-1/2 HDG	720 860	820 975	885 1060	740		
JUS26		LUS26	18	1-9/16	4-13/16	1-3/4	1	--	4	10d	4	10d	870	1000	1080	1050			
MUS26		MUS26	18	1-9/16	5-1/16	2	1	--	6	10d	6	10d	1310	1495	1620	865			
SUH26		U26	16	1-9/16	5-1/8	2	1-3/16	--	6	10d 16d	4	10d x 1-1/2	750 880	840 1000	910 1080	755			
HUS26		HUS26	16	1-5/8	5-7/16	3	2	--	14	16d	6	16d	2760	3140	3400	2045			
HD26		HU26	14	1-9/16	3-1/2	2-1/2	1-1/8	Min Max	4	16d	2 4	10d x 1-1/2	615	695	745	335 585			
HD28	HU28	14	1-9/16	5-1/4	2-1/2	1-1/8	--	8	16d	6	10d x 1-1/2	1230	1390	1490	760				
2 x 8	JL26	LU26	20	1-9/16	4-3/4	1-1/2	15/16	--	6	10d 16d	4	10d x 1-1/2	710 840	805 960	870 1045	600			
	JL26IF-TZ	LUC26Z	18	1-9/16	4-1/2	1-1/2	--	--	6	10d HDG 16d HDG	4	10d x 1-1/2 HDG	720 860	820 975	885 1060	740			
	JL28	LU28	20	1-9/16	6-3/8	1-1/2	15/16	--	10	10d 16d	6	10d x 1-1/2	1180 1400	1345 1600	1450 1740	815			
	JL28IF-TZ	--	18	1-9/16	6-1/8	1-1/2	--	--	8	10d HDG 16d HDG	4	10d x 1-1/2 HDG	960 1145	1095 1195	1180 1195	740			
	JUS26	LUS26	18	1-9/16	4-13/16	1-3/4	1	--	4	10d	4	10d	870	1000	1080	1050			
	JUS28	LUS28	18	1-9/16	6-5/8	1-3/4	1	--	6	10d	4	10d	1110	1270	1375	1050			
	MUS26	MUS26	18	1-9/16	5-1/16	2	1	--	6	10d	6	10d	1310	1495	1620	865			
	MUS28	MUS28	18	1-9/16	7-1/16	2	1	--	8	10d	8	10d	1745	1995	2160	1230			
	SUH26	U26	16	1-9/16	5-1/8	2	1-3/16	--	6	10d 16d	4	10d x 1-1/2	750 880	840 1000	910 1080	755			
	SUH28	--	16	1-9/16	6-5/8	2	1-3/16	--	8	10d 16d	6	10d x 1-1/2	1000 1175	1120 1335	1210 1440	875			
	HUS26	HUS26	16	1-5/8	5-7/16	3	2	--	14	16d	6	16d	2760	3140	3400	2045			
	HUS28	HUS28	16	1-5/8	7-3/16	3	2	--	22	16d	8	16d	4170	4745	5125	2990			
	HD28	HU28	14	1-9/16	5-1/4	2-1/2	1-1/8	--	8	16d	6	10d x 1-1/2	1230	1390	1490	760			
	HD210	HU210	14	1-9/16	7-3/16	2-1/2	1-1/8	Min Max	10 14	16d	4 6	10d x 1-1/2	1540 2155	1735 2430	1865 2610	760 1170			


1) Uplift loads have been increased 60% for wind or seismic loads; no further increase shall be permitted.

2) For JUS, HUS, and MUS hangers: Nails must be driven at a 30° to 45° angle through the joist or truss into the header to achieve the table loads.

3) **NAILS:** 10d x 1-1/2 nails are 0.148" dia. x 1-1/2" long, 10d nails are 0.148" dia. x 3" long, 16d nails are 0.162" dia. x 3-1/2" long.

New products or updated product information are designated in **blue font**.

Corrosion Finish Key ■ Stainless Steel ■ Gold Coat ■ HDG ■ Triple Zinc



Continued on next page